

ALBERTI[®]
INTERNATIONAL
PROFESSIONAL LINE

IDRO HOT



ALBERTI[®]
INTERNATIONAL

IDROHOT
PROFESSIONAL LINE



Via Galileo Galilei c.m.
46020 Motteggiana - Mantova - ITALY -
Tel. ++39 0376 510 065 | Fax ++39 0376 510 034
www.alberti-international.it | info@alberti-international.it

•Delayed Total Stop device

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- High pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Micro-leaks control
- Flame control device
- 24V controls
- Stainless steel boiler

Accessories Optional:

- Hose reel
- Magnetic scale preventing device
- Scale preventing device
- Rotating nozzle
- Sandblaster
- Pipe jet nozzle
- Remote Control
- Stainless Steel Frame



•Total Stop Temporizzato

Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Disp. deterg. in alta pressione
 - Pompa alta pressione con testata in ottone e pistoni in ceramica
- Controllo micro perdite
 - Controllo fiamma
 - Comandi a 24V
- Caldaia in acciaio inox

Accessori Optional:

- Avvolgitubo
- Anticalcare magnetico
- Anticalcare Chimico
- Ugello rotante
- Kit per idrosabbatura
- Testina sturatubi
- Controllo a Distanza
- Telaio in acciaio inox

IDRO HOT	120/10	170/13	150/15	200/15	150/21	200/21
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	1260l/h
Max Water Temp.	0-140°C	0-140°C	0-140°C	0-140°C	0-140°C	0-140°C
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP	7,5 HP	10 HP
Dimensions mm	680x580x1050	680x580x1050	680x580x1050	680x580x1050	680x580x1050	680x580x1050
Weight	122 kg	130 Kg	130 Kg	135 Kg	135 Kg	148 Kg